

Product Class	Heating elements B59xxxA/R/U*
Date	23.11.2021
IMDS ID if available	
Version	5.38

Product Part (IMDS: semi component)	Material Class (IMDS: Material)	Material (Classification) VDA 231	Substance	TMPS**) [wt%]	CAS if applicable	typical mass of material [wt-%]	Traces see 1)
Active Part	Ceramic	3B	Ba-titanates	69	12047-27-7	98,5	
			Pb-titanates	15	12060-00-3		
			Sr-titanates	10	12060-59-2		
			Ca-titanates	5	12049-50-2		
			others*)	1			
Termination	Composite	4D	Ag	95	7440-22-4	1,42	
			Glass frit (lead-boro-silicate)	5			
	Heavy Metal	1C14	Ni	100	7440-02-0	0,05	
	Heavy Metal	1C2	Cr	100	7440-47-3	0,03	
Sum of total						100	

sizes [mm]	weight range[g]	material numbers	sizes [mm]	weight range[g]	material numbers
5 x 4 x 1.6	0.2	B59010R1*	4,2 x 1,05	0,08	B59014A0270B040
15 x 5 x 2	2,68	B59011U0180B010	5 x 1.1	0.117	B59016A0080A*
35 x 6.2 x 1.4	1.7	B5904xR*	8 x 1	0.3	B59022A1*
17.5 x 6.2 x 1.1	0.72	B59074R*	12 x 2	1.3	B59046U0070B010
17.5 x 6.2 x 1.1	0.72	B59076R*	12 x 2	1.2	B59047U*
27.3 x 13 x 1.4	2,77	B59078R0145B*	8 x 3	0.8	B59053A*
27.3 x 13 x 1.4	2,77	B59079R0145B*	8 x 3	0.9	B59054A*
9 x 6,5 x 1,4	0,5	B59096R0100B010	8 x 3	0,9	B59054A0210B110
35 x 6.2 x 2	2.4	B59101R*	12 x 1	0.6	B59060A*
35.4 x 14.5 x 1.4	4.0	B59130R*	12 x 1.1	0.7	B59061A*
34.9 x 5.7 x 1.15	1.2	B59149R*	12 x 1	0.6	B59062A*
35 x 25 x 5	34,3	B59155R0270B010	6,4 x 3	0,6	B59064A0210B110
35 x 35 x 3,2	21,9	B59155R0270B110/B210	12 x 2	1,2	B59065A*
36,2 x 5,7 x 0,9	1,2	B59179R*	10 x 2,2	1	B59097A*
35 x 8 x 1,4	2,2	B59201R*	10 x 2,2	1	B59099A*
35 x 8 x 1,4	2,2	B59204R*, B59205R*, B59206R*, B59207R*	12 x 1,5	0,9	B59123A0130B010
35 x 8 x 1,4	2,2	B59205R0140B*	12 x 1,3	0,8	B59124U0140B010
35 x 8 x 1,4	2,2	B59206R0150B010	10 x 1,5	0,66	B59126A1160B010
35 x 8 x 1,4	2,2	B59207R0140B010	12 x 1,5	0,9	B59130A*
35 x 8 x 1,4	2,2	B59208R0140B210	14 x 1	0,86	B59141A*
35 x 8 x 2,1	3,32	B59209R0150B010	14 x 1,1	0,97	B59142A0145B*
35 x 14,5 x 1,4	3,9	B59220R*	16 x 1,5	1,7	B59161A*
28.8 x 13.2 x 2	3.5	B59293R*	16 x 1,5	1,7	B59161U0120B010
28.8 x 13 x 2	3,45	B59295R*	16 x 1,1	1,2	B59164A0150B010
29 x 5,8 x 1	0,94	B59305U0160B010	12 x 2	1,2	B59660A*
29 x 5,8 x 1	0,94	B59305U0160B010	12 x 2	1,3	B59669A0070B010
27.8 x 10.6 x 4.0	6.8	B59340R*	12 x 2	1,2	B59669A0080B010
35 x 14.5 x 1.4	3.9	B59388R*	12 x 2	1,2	B59671A*
35 x 14.5 x 1.4	3.9	B59388U*	12 x 2	1,2	B59673A*
11 x 11 x 1.1	0.74	B59391R*	12 x 2	1,2	B59679A*
35 x 14.5 x 2,2	6,4	B59393R0140B010	12 x 2	1,35	B59682A0100B010
17.5 x 14.5 x 1.1	1.55	B59394R*	12 x 2,1	1,4	B59688A0055B010
14,5 x 14,5 x 1,4	1,6	B59396R110B10	12 x 1	0,6	B59691A0120B010
28.8 x 9.8 x 1.4	2.21	B59441R0130B*	12 x 2	1,2	B59692A0080B010
28.8 x 8 x 1.1	1.5	B59501R*	12 x 1	0,6	B59693A0120B010
28.8 x 8 x 1,1	1,46	B59502R0140B210	12 x 1,3	0,8	B59695A*
28.8 x 8 x 1,1	1,46	B59503R0140B110	12 x 2,1	1,2	B59696A*
28.8 x 8 x 1,1	1,5	B59504R*	12 x 2,1	1,2	B59697A0080B010
			7,6 x 1,47	0,4	B59728A0100B010
			8 x 2.5	0.75	B59870A*
			8 x 2.5	0.75	B59875A*

Not part of a Product Class

Product Class	Heating elements B59xxxA/R/U*
Date	23.11.2021
IMDS ID if available	
Version	5.38

Contact	Ronner Christoph	Important remarks: 1) The declaration limit is 0.1% as defined by IEC 62474 (IEC PAS 61906). Traces are product parts, substances etc. that are below a percentage of 0.1 % by weight, if not otherwise regulated. 2) This Material Data Sheet contains typical values of the respective products set forth herein. We expressly point out that all values and statements contained herein are based on our best present knowledge and cannot be regarded as binding statements or binding product specifications, unless otherwise explicitly agreed in writing. TDK ELECTRONICS AG AND ITS AFFILIATES HEREBY EXPRESSLY DISCLAIM ANY REPRESENTATION OR WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY, WITH REGARD TO THE STATEMENTS AND VALUES CONTAINED HEREIN, INCLUDING BUT NOT LIMITED TO ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PURPOSE.
Division	PPD Q QM	
Address	8530 Deutschlandsberg, AUSTRIA	
	Tel: +43 3462 800 2139 mailto: functional_ppd-epqm.db@tdk-electronics.tdk.com	
*) others: not declarable or prohibited substances acc. GADSL **) typical mass percentage of substance		

The products set forth herein are "RoHS-compatible". RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8th, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

RoHS - Exemptions for the Product Class / Product according to Annex III: (valid not valid)

- no exemptions;
- Exemption 6 (a): Lead as an alloying element in steel for machining purposes and in galvanized steel containing up to 0,35 % lead by weight;
- Exemption 6 (b): Lead as an alloying element in aluminium containing up to 0,4 % lead by weight;
- Exemption 6 (c): Copper alloy containing up to 4 % lead by weight;
- Exemption 7 (a): Lead in high melting temperature type solder (i.e. lead-based alloys containing 85 % by weight or more lead);
- Exemption 7 (c)-I: Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectric devices, or in a glass or ceramic matrix compound;
- Exemption 7 (c)-II: Lead in dielectric ceramic in capacitors for a rated voltage of 125 V AC or 250 V DC or higher;
- Exemption 7 (c)-III: Lead in dielectric ceramic in capacitors for a rated voltage of less than 125 V AC or 250 V DC;
- Exemption 15: Lead in solders to complete a viable electrical connection between semiconductor die and carrier within integrated circuit Flip Chip packages;
- Other Exemption than above